

# Safety Data Sheet

1250 Dye Ink

---

## SECTION 1 *Product Identification and General Information*

---

**Manufactured for:** Hitt Marking Devices 3231 W. MacArthur Blvd., Santa Ana, CA 92704

**Product Information:** 800-969-6699

**Emergency Contact /Phone Number (24 Hour):** Chemtrec 1-800-424-9300 (for chemical emergencies)

**Emergency Phone Number (Outside U.S. and Canada):** Chemtrec +01-703-527 3887

**Product Numbers:** 1250 Dye Ink (black, white, blue, green, red, violet, brown)

**Chemical Name:** 1250 Dye Ink

**Date MSDS Prepared:** 9/25/2022

This MSDS has been prepared for the purposes of Hazard Communication, under 29 CFR 1910.1200.

---

## SECTION 2 *Hazards Identification*

---

**EMERGENCY OVERVIEW:** Danger! Flammable liquid, Target Organ Effect, Harmful by Skin Absorption. Explosive peroxides may form on prolonged storage in contact with air and heat.

**Target Organs:** Nerves, Liver, Heart, Lungs, Blood, Kidney, Male Reproductive System, Bone marrow

**GHS Classification:** Flammable liquids; Skin irritation; Eye irritation; Specific target organ toxicity

**GHS Label Elements, including Precautionary Statements:**



**Pictograms :**

**Signal Word:** Danger

**Hazard Statements :** Highly Flammable liquid and vapor.

Causes skin and eye irritation.

May cause respiratory irritation.

Suspected of damaging fertility or the unborn child.

**Precautionary Statements:** Keep away from heat/sparks/open flames/hot surfaces . No smoking.

Do not breathe dust/ fume/ gas/ mist/ vapors/ spray.

Use personal protective equipment as required.

IF SWALLOWED: Immediately call a POISON CENTER or doctor/ physician.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

**Potential Health Effects:**

**Inhalation:** May be harmful if inhaled. Causes respiratory tract irritation. Vapors may cause drowsiness and dizziness.

**Skin:** May be harmful if absorbed through skin. Causes skin irritation.

**Eyes:** Causes eye irritation.

**Ingestion:** May be harmful if swallowed. Aspiration hazard if swallowed - can enter lungs and cause damage.

**Primary Routes of Entry:** Inhalation, skin absorption, skin contact, and eye contact.

**Chronic Exposure:** May cause reproductive and fetal effects (Ethanol). Laboratory experiments have resulted in mutagenic effects. Animal studies have reported the development of tumors. Prolonged exposure may cause liver, kidney, and heart damage.

**Target Organs:** Kidneys, heart, central nervous system, liver.

**Pre-Existing Conditions:** May aggravate persons with pre-existing skin disorders, digestive, liver, and kidney problems.

**SECTION3** *Composition/Information on Ingredients*

Contents	Percent by Weight	CASNo.	OSHA PEL	ACGIH TLV	LISTED CARCINOGEN (IARC/OSHA/NTP)
Ethanol	30% - 35%	64-17-5	1000 ppm	1000 ppm	No
Ethylene Glycol Monomethyl Ether	35% - 40%	107-98-2	25 ppm	0.1 ppm	No
Diacetone Alcohol	20% - 25%	123-42-2	50 ppm	50 ppm	No
Modified Polymers/Binders	5% - 10%	Proprietary			No
4-(phenylazo)benzene-1,3-diamine	1% - 2%	495-54-5			No
Rhodamine B, O	1% - 2%	81-88-9			No

There is no toxicity data available for this mixture. The hazards associated with overexposure to this mixture are assumed to be due to exposure to the components.

**SECTION4** *First Aid Procedures*

**Eye Contact:** Flush with copious amounts of water for at least 15 minutes, lifting lower and upper eyelids occasionally. Get medical attention.

**Skin Contact:** In case of contact, immediately flush skin with plenty of soap and water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. Call a physician immediately.

**Inhalation:** If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Call a physician immediately.

**Ingestion:** Inducing vomiting should only be performed under the direct supervision of medical supervision. Never give anything by mouth to an unconscious person. Call a physician or Poison Control Center immediately.

**SECTION5** *Fire-Fighting Measures*

**Flash Point:** <70°F

**Fire and Explosion Hazards:** Flammable Liquid. Dangerous re-hazard when exposed to heat or Flame.

**Extinguishing Media:** Water spray, foam, dry chemical, carbon dioxide. Alcohol resistant foams (ATC) are preferred, if available.

**Special Fire Fighting Procedures:** In the event of a fire, wear full protective clothing and NIOSH-approved self-contained breathing apparatus with full face piece operated in the pressure demand or other positive pressure mode. Water spray may be used to keep re-exposed containers cool.

**Unusual Fire and Explosion Hazards:** This flammable liquid must be kept away from sparks, open flame, hot surfaces, and all sources of heat and ignition. Decomposition materials may emit acrid smoke and irritating fumes. Never use welding or cutting torch on or near drum (including empty) because product can ignite explosively.

---

**SECTION6***Accidental Release Measures*

---

**Spill Procedure:** Ventilate area of leak or spill. Remove all sources of ignition. Wear appropriate personal protective equipment. Isolate hazard area. Keep unnecessary and unprotected personnel from entering. Contain and recover liquid when possible. Use non-sparking tools and equipment. Collect liquid in an appropriate container or absorb with an inert material (i.e., vermiculite, dry sand, and earth), and place in a chemical waste container. Do not use combustible materials, such as sawdust. Do not flush to sewer! If leak or spill has not ignited, use water spray to disperse the vapors, to protect personnel attempting to stop leak, and to flush spills away from exposures.

US Regulations (CERCLA) require reporting spills and releases to soil, water, and air in excess of reportable quantities.

---

**SECTION7***Handling and Storage*

---

**Precautions:** Protect against physical damage. Store in a cool, dry well-ventilated location, away from any area where the re-hazard may be acute. Separate from incompatibles. Containers should be bonded and grounded for transfers to avoid static sparks. Storage and use areas should be NO SMOKING areas. Use nonsparking tools and equipment, including explosion proof ventilation. Containers of this material may be hazardous when empty since they retain product residues (vapors, liquid); observe all warnings and precautions listed for the product.

---

**SECTION8***Exposure Controls/Personal Protection*

---

**Eye Protection:** Use chemical safety glasses or goggles and/or a full face shield where splashing is possible. Maintain eye wash fountain and quick-drench facilities in work area.

**Ventilation System:** A system of local and/or general exhaust is recommended to keep employee exposures below the Airborne Exposure Limits. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at its source, preventing dispersion of it into the general work area. Use explosion-proof equipment.

**Respiratory Protection:** Appropriate respiratory protection is required when exposure to airborne contaminant is likely to exceed acceptable limits. Respirators should be selected and used in accordance with OSHA Part 1910.134 and manufacturer's recommendations.

**Skin Protection:** Wear impervious protective clothing, including boots, gloves, lab coat, apron or overalls, as appropriate, to prevent skin contact. Check with your safety supplier for the proper chemical-resistant gloves.

---

**SECTION9***Physical and Chemical Properties*

---

**Appearance:** Colored Liquids

**Odor:** Alcohol - like odor

**Vapor Density:** >1 (Air = 1)

**Physical State:** Liquid

**Specific Gravity:** >1 (Water = 1)

---

**SECTION10***Stability and Reactivity*

---

**Stability:** Under normal storage conditions, peroxidizable compounds can form and accumulate peroxides which may explode when subjected to heat or shock. This material is most hazardous when peroxide levels are concentrated by distillation or evaporation.

**Conditions to Avoid:** Heat, flames, sparks, ignition sources and incompatibles.

**Incompatibility (materials to avoid):** Oxidizing materials.

**Hazardous Decomposition Products:** Carbon dioxide and carbon monoxide may form when heated to decomposition.

**Hazardous Polymerization:** Will not occur.

---

**SECTION11** *Toxicological Information*

---

**Toxicological Data:** There is no available data for the product itself.

---

**SECTION12** *Ecological Information*

---

**Environmental Toxicity:** The ecological characteristics of this product have not been fully investigated. The product should not be allowed to enter drains or water courses or be deposited where it can affect ground or surface waters. Do not discharge product into the environment.

---

**SECTION13** *Disposal Considerations*

---

**Waste Disposal Method:** Recovered non-usable material may be regulated as a hazardous waste due to its ignitibility and/or its toxic characteristics. It is the responsibility of the user to determine if the material is a RCRA "hazardous waste" at the time of disposal. Transportation, treatment, storage, and disposal of waste material must be conducted in accordance with RCRA regulations. State and/or local regulations may be more restrictive.

---

**SECTION14** *Transport Information*

---

**USDOTand IMDGRegulations**

Proper Shipping Name – UN1210, Printing Ink, 3, PG II  
Hazard Class – 3 (Flammable Liquid)  
Identification Number – UN1210  
Label Required – Flammable

**IATA Regulations**

Proper Shipping – UN1210, Printing Ink, 3, PG II

---

**SECTION15** *Regulatory Information*

---

**Toxic Substances Chemical Inventory (TSCA):** This product (and/or all of its components) is in compliance with USEPA TSCA.

---

**SECTION16** *Other Information*

---

**HMISHazard Rating:** Health – 2; Fire – 3; Reactivity – 0; PPE – Goggles & Shield; Apron; Proper Gloves; Fire Extinguisher

**MSDSPreparation Date:** 9/25/2022

---

**DISCLAIMER:**

The information accumulated herein is believed to be accurate and represents the best data currently available. It is the user's responsibility to determine suitability of use. No warranty, expressed or implied, is made and Hitt Marking Devices assumes no legal responsibility or liability resulting from its use. Materials comprising <1% by weight, or <0.1% by weight if the chemical is a carcinogen, are not listed herein.