Safety Data Sheet

8300 Colored Inks

SECTION 1 Product Identification and General Information

Manufactured for: Hitt Marking Devices

Manufacturer Address: 3231 W. MacArthur Blvd., Santa Ana, CA 92704

Product Information: 714-979-1405

Emergency Phone Number (24 Hour): Infotrac 1-800-535-5053 for Domestic USA(For Hazardous Materials (or Dangerous

Goods) Incident, Spill, Leak, Fire, Exposure or Accident.

Emergency Phone Number (Outside U.S. and Canada): Infotrac 1-325-323-3500(collect calls accepted)

Product Numbers: 8300 Colored Inks (Black, Blue, Red, Green, and White)

Product Use: Printing Inks
Date SDS Prepared 08/06/2024

This SDS has been prepared for the purposes of Hazard Communication, under 29 CFR 1910.1200.

SECTION 2 Hazards Identification

EMERGENCY OVERVIEW: Danger! Flammable liquid, Target Organ Effect, Irritant.

Target Organs: Central Nervous System

GHS Classification: Flammable liquids (Category 2) Eye irritation (Category 2A); Acute toxicity, Oral (Category 4);

Skin irritation (Category 2);

Specific target organ-toxicity single exposure (Category 3), Central Nervous System

GHS Label Elements, including Precautionary Statements:





Pictograms:

Other Hazards

Date Prepared:08/06/2024

Signal Word Danger

Hazard Statements: Highly flammable liquid and vapor.

Causes skin and eye irritation.

May cause drowsiness or dizziness.

Precautionary Statements: Keep away from heat/sparks/open flames/hot surfaces. No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ ventilating/ lighting/ equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge. Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.

Wash skin thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/ eye protection/ face protection.

IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a

POISON CENTER/doctor if you feel unwell.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

8300 Colored Inks SDS

present and easy to do. Continue rinsing.

Page1 of 4

If eye irritation persists: Get medical advice/ attention. Repeated exposure may cause skin dryness or cracking.

SECTION 3 Composition/Information on Ingredients						
Contents	Synonyms	Percent by Weight	CAS No	OSHA PEL	ACGIH TLV	LISTED CARCINOGEN (IARC/OSHA/NTP)
Ethanol	Ethyl Alcohol	20% - 30%	64-17-5	1000 ppm	1000 ppm	No
Diacetone Alcohol		15%- 20%	123-42-2	50 ppm	50 ppm	No
1-Methoxy-2-Propanol		5% - 15%	107-98-2		100 ppm	No
n-Butanol	Butyl Alcohol	20% - 25%	71-36-3	100 ppm	20 ppm	No
2-Propoxyethanol		50% - 55%	2807-30-9			No
Modified Polymers/Binders	•	10% - 15%	Proprietary			No
Ethyl Acetate		2% – 6%	141-78-6	400 ppm	400 ppm	No
Isopropanol	2-Propanol	2% - 6%	67-63-0	400 ppm	200 ppm	IARC 3 (See Section 11)
Nitrocellulose		2% - 6%	900470-0			No
Colored Pigments		1% - 5%	Proprietary			No

SECTION 4 First Aid Procedures

Description of First Aid Measures

Eye Contact: Flush with copious amounts of water for at least 15 minutes, lifting lower and upper eyelids occasionally. Get medical attention.

Skin Contact: In case of contact, immediately flush skin with plenty of soap and water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. Call a physician immediately.

Inhalation: If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Call a physician immediately.

Ingestion: Inducing vomiting should only be performed under the direct supervision of medical personnel. Never give anything by mouth to an unconscious person. Call a physician or Poison Control Center immediately.

Most important symptoms and effects, both acute and delayed The most important known symptoms and effects are described in the labeling (see Section 2) and/or in Section 11

Indication of any immediate medical attention and special treatment needed: No data available.

SECTION 5 Fire-Fighting Measures

Flash Point:<70°F

Fire and Explosion Hazards: Flammable Liquid. Dangerous fire hazard when exposed to heat or flame.

Extinguishing Media: Water spray, foam, dry chemical, carbon dioxide. Alcohol resistant foams (ATC) are preferred, if available.

Special Hazards arising from the Substance Mixture:

Fire Fighting Procedures: In the event of a fire, wear full protective clothing and NIOSH approved self contained breathing apparatus with full face piece operated in the pressure demand or other positive pressure mode. Water spray may be used to keep fire-exposed containers cool.

Unusual Fire and Explosion Hazards: This flammable liquid must be kept away from sparks, open flame, hot surfaces, and all sources of heat and ignition. Decomposition materials may emit acrid smoke and irritating fumes. Never use welding or cutting torch on or near drum (including empty) because product can ignite explosively.

SECTION 6 Accidental Release Measures

Personal precautions, protective equipment and emergency procedures Use personal protective equipment. Avoid breathing vapors, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas. For personal protection see section 8.

Environmental precautions Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

Methods and materials for containment and cleaning up Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see section 13).

Reference to other sections For disposal see section 13.

SECTION 7 Handling and Storage

Precautions for Safe Handling: Protect against physical damage. Store in a cool, dry well ventilated location, away from any area where the fire hazard. Separate from incompatibles. Storage and use areas should be NO SMOKING areas.-Use non sparking tools and equipment. Containers of this material may be hazardous when empty since they retain product residues (vapors, liquid); observe all warnings and precautions listed for the product.

Conditions for Storage Store in a cool, dry, well ventilated place, in securely closed original container. Flammable/combustible - Keep away from oxidizing agents, heat and flames.

Specific End Uses: Apart from the uses mentioned in Section 1 no other specific uses are stipulated

SECTION 8

Exposure Controls/Personal Protection

Ingredients	CAS No	OSHA PEL	ACGIH TLV
Ethanol	64-17-5	1000 ppm	1000 ppm
Diacetone Alcohol	123-42-2	50 ppm	50 ppm
1-Methoxy-2-Propanol	107-98-2		100 ppm
n-Butanol	71-36-3	100 ppm	20 ppm
Ethyl Acetate	141-78-6	400 ppm	400 ppm
Isopropanol	67-63-0	400 ppm	200 ppm

Eye Protection: Use chemical safety glasses or goggles and/or a full face shield where splashing is possible. Maintain eye wash fountain and quickdrench facilities in work area.

Ventilation System: A system of local and/or general exhaust is recommended to keep employee exposures below the Airborne Exposure Limits. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at its source, preventing dispersion of it into the general work area. Use explosion-proof equipment.

Respiratory Protection: Appropriate respiratory protection is required when exposure to airborne contaminant is likely to exceed acceptable limits. Respirators should be selected and used in accordance with OSHA Part 1910.134 and manufacturer's recommedations.

Skin Protection: Wear impervious protective clothing, including boots, gloves, lab coat, apron or overalls, as appropriate, to prevent skin contact. Check with your safety supplier for the proper chemical resistant gloves.

SECTION 9

Physical and Chemical Properties

Appearance: Liquid Color: Colored Odor/Taste: Alcohol like

Odor Threshold: Not Determined

pH: Not Determined

Solubility Description: Partially Soluble In Water.

Boiling Point (°C@760 mmHg): 70 Melting Point (°F/°C): Not Determined Auto ignition Temperature: Not Determined

Partition Coefficient (noctanol/water): Not Determined

Explosive Properties: Not Determined

Flashpoint:<70°F

Flammability (solid, gas): Not Determined Upper/Lower Flammability Not Determined

Freezing Point (°F/°C): -124° /-86°

Specific Gravity (@68°F, Water=1): ~0.90

Vapor Density (Air=1):>2.5

Vapor Pressure (mmHg@68° F): <70

Viscosity: Not Determined

Evaporation Rate (Butyl Acetate=1):~1

Decomposition Temperature Not Determined

Oxidizing Properties: Not Determined

SECTION 10

Stability and Reactivity

Reactivity: No data available.

Stability: Stable.

Possibility of Hazardous Reactions:

Conditions to Avoid: Heat, flames, sparks, ignition sources and incompatibles.

Incompatibility (materials to avoid): Oxidizing materials.

Hazardous Decomposition Products: Carbon dioxide and carbon monoxide may form when heated to decomposition.

Hazardous Polymerization: Will not occur.

SECTION 11 Toxicological Information

No toxicity studies have been conducted on this product. As with all chemicals for which test data are limited or do not exist, caution must be exercised through the prudent use of protective equipment and handling procedures to minimize exposure.

Potential Symptoms and Effects:

Inhalation: May be harmful if inhaled. Causes respiratory tract irritation. Vapors may cause drowsiness and dizziness.

Skin: May be harmful if absorbed through skin. Causes skin irritation.

Eyes: Causes eye irritation.

Ingestion: May be harmful if swallowed.

International Agency for Research on Cancer ("IARC") Classification for Isopropanal

Isopropanol is classified as IARC Group 3 or Unclassifiable as Carcinogenic to Humans.

No components of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP or OSHA.

SECTION 12 Ecological Information

Environmental Toxicity: The ecological characteristics of this product have not been fully investigated. The product should not be allowed to enter drains or water courses or be deposited where it can affect ground or surface waters. Do not discharge product into the environment.

SECTION 13 Disposal Considerations

Waste Disposal Method: Recovered non-usable material may be regulated as a hazardous waste due to its ignitibility and/or its toxic characteristics. It is the responsibility of the user to determine if the material is a RCRA "hazardous waste" at the time of disposal. Transportation, treatment, storage, and disposal of waste material must be conducted in accordance with RCRA regulations. State and/or local regulations may be more restrictive.

SECTION 14 Transport Information

USDOT and **IMDG** Regulations

Proper Shipping Name–UN1210, Printing Ink, 3, PG II Hazard Class–3 (Flammable Liquid) Identification Number–UN1210 Label Required – Flammable

IATA Regulations

Proper Shipping – UN1210, Printing Ink, 3, PG II

SECTION 15 Regulatory Information

Toxic Substances Chemical Inventory (TSCA): This product (and/or all of its components) iscimpliance with USEPA TSCA.

SECTION 16 Other Information

HMIS Hazard Rating: Health-2; Fire-3; Reactivity-0; PPE-Goggles & Shield; Apron; Vent Hood; Proper Gloves; Fire Extinguisher

SDS Preparation Date: 08/06/2024

DISCLAIMER:

The information accumulated herein is believed to be accurate and represents the best data currently available. It is the user's responsibility to determine suitability of use. No warranty, expressed or implied, is made and Hitt Marking assumes no legal responsibility or liability resulting from its use. Materials comprising <1% by weight,or <0.1% by weight if the chemical is a carcinogen,are not listed herein.